

PU EPOLLO

PVC HELIX

Anti-Static Suction Hose
Food Grade



Epollo Anti-static Polyurethane with a Rigid PVC Helix (with a copper braid) features a smooth bore and transparent wall with excellent abrasion and chemical resistance.

Superior tear resistance providing durability.

Colour: Yellow/Transparent Temperature Range: -40°C to 120°C Material: Polyurethane	NOM I.D (inch)	NOM I.D (mm)	NOM O.D (mm)	Bend Radius (mm)	Vacuum (kPa _g)	Weight (kg/m)	Coil (m)
Applications: - Granule & seed Transport - Industrial Vacuum cleaners - Food Packaging equipment - Woodworking & Furniture Industries - Dust Collection equipment - Fume Exhaust -Fertilizer Broadcasting	1	25	33	33	-25	0.15	20
	1 ½	38	48	48	-20	0.22	20
	2	51	69	69	-20	0.32	20
	2 ½	63	78	78	-16	0.51	20
	3	76	89	89	-16	0.60	20
	4	102	120	120	-13	0.83	20

*Other sizes available upon request

Plascorp Brisbane
(07) 3035 9200
salesqld@plascorp.com.au

Plascorp Melbourne
(03) 9319 6400
sales@plascorp.com.au

Plascorp Perth
(08) 6278 9400
wasales@plascorp.com.au

PLASTICOAT™ Ducting
CODEMASTER™ Composite Hose
REOMASTER™ Steel Reinforcement
MINEMASTER™ Mine Ventilation
PIPEMASTER™ PVC Pipe

TELEPHONE 1300 301313
www.plascorp.com.au

ABN 34 096 078 527

 **PLASCORP™**