

# SILICONE DUCTING

*Hi-Temp*



Double-ply silicone coated fiberglass fabric hose reinforced with a spring steel wire helix and external filament fiberglass cord. Extremely flexible and lightweight.

Suitable for high temperature air handling applications.

Narrow pitch allows for a tight bending radius that is non-kinking while maintaining a smooth airflow.

Not recommended for continuous flexing.

Resistant to many oils and solvents, ozone, water, fungus & alkalis.

Colour: Orange Temperature Range: -70°C to 310°C Material: Silicone-coated glass fabric	NOM I.D (inch)	NOM I.D (mm)	NOM O.D (mm)	Bending Radius (mm)	Working Pressure (kPa <sub>g</sub> )	Weight (kg/m)	Coil (m)
<b>Applications:</b> - Automotive - Brake Ducting - Heater Hose - Dry Cleaning - Exhaust Systems - Transmission Cooling - High Temperature Glass Drying - Plastic processing	1	25	30	30	280	0.19	4
	1 ½	38	43	43	260	0.23	4
	2	51	56	56	260	0.30	4
	3	76	81	81	210	0.43	4
	4	102	107	107	190	0.63	4

\*Other sizes available upon request

Plascorp Brisbane  
(07) 3035 9200  
salesqld@plascorp.com.au

Plascorp Melbourne  
(03) 9319 6400  
sales@plascorp.com.au

Plascorp Perth  
(08) 6278 9400  
wasales@plascorp.com.au

PLASTICOAT™ Ducting  
CODEMASTER™ Composite Hose  
REOMASTER™ Steel Reinforcement  
MINEMASTER™ Mine Ventilation  
PIPEMASTER™ PVC Pipe

TELEPHONE 1300 301313  
www.plascorp.com.au

ABN 34 096 078 527

 **PLASCORP™**